

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 26 S., R. 3 W.

CHAINS		
	S of R. 4 W., and ran a true line E on the S bdy. of sec. 31 in T. 26 S., R. 3 W.	
	Va.17*30'E.	
	East, on true South bdy. of sec. 31.	
	Va.17*30'E.	
6.39	Enter J. A. Abbott's improvements.	
16.00	Stone house, 150 lks. S of line.	+20
23.00	House, 300 lks. S of line.	
27.75	Left improvement.	+20
40.00	Set $\frac{1}{4}$ sec.post, from which	
	A W. oak, 8 ins. diam., bears N.5*W., 350 lks. dist.	
	An ash, 8 ins. diam., bears S.38*E., 164 lks. dist.	
55.00	Trail SE.	
78.00	Summit of ridge, N and S.	
80.00	Set post, cor. to secs. 31, 32, 5 and 6, from which	+85
	A W. oak, 8 ins. diam., bears N.23*W., 55 lks. dist.	-15
	A B. oak, 15 ins. diam., bears N.18*E., 79 lks. dist.	
	A B. oak, 18 ins. diam., bears S.60*E., 22 lks. dist.	
	A B. oak, 5 ins. diam., bears S.61*W., 104 lks. dist.	
	Land, 2d rate.	
	Timber, oak, pine and laurel.	
	East, on true South bdy. of sec. 32.	
	Va.17 $\frac{1}{2}$ *E.	
10.45	Trail, NE.	
40.00	Set $\frac{1}{4}$ sec. post, from which	-100
	A B. oak, 7 ins. diam., bears N.49*W., 37 lks. dist.	
	A W. oak, 7 ins. diam., bears S.27*E., 89 lks. dist.	
41.00	Enter fir timber.	
44.45	"Fall Creek" 25 lks. wide, runs N.	-10
47.00	Left fir timber.	