


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS		
39.70	Set $\frac{1}{4}$ sec. post, around which a mound of stones were raised, as per instructions.	+50
67.50	Ravine, running NW.	-75
73.50	Summit of ridge.	+100
79.40	The cor. of secs. 16, 17, 20 and 21. Land, 3d rate, broken into ridges N and S. Timber, principally fir, some oak, cedar, maple, ash and laurel, underbrush.	
North, on line, bet. secs. 16 and 17.		
Va.17*45'E.		
40.00	Set $\frac{1}{4}$ sec. post, from which A red fir, 5 ins. diam., bears S.11*W., 13 lks. dist. A red fir, 6 ins. diam., bears N.15*E., 19 lks. dist.	-100
41.75	Trail, E and W.	-10
53.25	Trail, E and W. 	-30
54.75	North Umpqua River, 4.89 lks. wide, runs SW; enter prairie at N bank of river.	
80.00	To post cor. of secs. 8, 9, 16 and 17, ^{around} which a mound was raised with stones, as per instructions. Land, on S side river, 3d rate; on N side, 1st rate. Timber, S side, fir, oak and laurel; N side of river, scattering pine, oak and laurel.	
East, on random line, bet. secs. 9 and 16.		
Va.17*30'E.		
40.00	Set temp. $\frac{1}{4}$ sec. post and	
79.25	Intersected N and S line, 68 lks. N of cor. of secs. 9 and 16, from which I run West, on true line, bet. secs. 9 and 16, course N.89*31'W.	