

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS		
	West, on random, bet. secs. 19 and 30.	
40.00	Set temp. $\frac{1}{4}$ sec. post and	
80.55	Intersected W bdy. of tp. at post, cor. of secs. 19 and 30 from which cor. I run	
	East, on true line, bet. secs. 19 and 30.	
20.00	Enter fir timber.	-25
21.00	Trail, N and S.	
22.75	Brook, 6 lks. wide, runs NW.	-30
23.25	Trail, N and S; leave fir timber.	
34.50	Enter improvement of Mr. Noland.	-15
40.55	Set $\frac{1}{4}$ sec. post, from which	
	A W. oak, 15 ins. diam., bears N.4*W., 347 lks. dist.	
	A W. oak, 8 ins. diam., bears S.74*E., 130 lks. dist.	
45.00	To East Fork of N. Umpqua, 250 lks. wide, runs NW.	
50.50	Enter improvement.	
76.50	Leave improvement.	
80.55	The cor. to secs. 19, 20, 29 and 30.	
	Land, East part, 1st rate; West part, 2d rate.	
	Timber, fir, pine, oak and laurel.	
	North, on line, bet. secs. 19 and 20.	
		Va.17*E.
38.60	Leave prairie.	
40.00	Set $\frac{1}{4}$ sec. post, from which	+25
	A B. oak, 15 ins. diam., bears S.75*E., 67 lks. dist.	
	A pine, 28 ins. diam., bears N.78*W., 78 lks. dist.	
66.00	Enter prairie.	
80.00	Set post cor. to secs. 17, 18, 19 and 20, around which a mound was raised, as per instructions. No trees being convenient.	-25