


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS	
40.00	Set temp. $\frac{1}{4}$ sec. post and
80.00	Intersected W bdy. of tp., 48 lks. S from cor. to secs. 18 and 19, from which cor. I run East, on true line, bet. secs. 18 and 19. Course, S.89*39'E.
26.75	N Umpqua river, 335 lks. wide, runs W of S. Distance across the river obtained as follows, viz:  Measured A.D. = 150 lks. constructed C.A.B. and A.D.C. right angle, then by simalarity of triangles (after measuring C.D.=67-2/10) we have 67-2/10: 150: 150: 335
40.00	Set $\frac{1}{4}$ sec. post, from which A red fir, 28 ins. diam., bears S.53*E., 38 lks. dist. A B. oak, 15 ins. diam., bears N.35*E., 68 lks. dist.
74.00	Trail, SW and NE.
80.00	The cor. to secs. 17, 18, 19 and 20. Land, on East part, 1st rate; on the West part, 2d rate. Timber, oak, fir, pine and laurel.
6.00	North, on line, bet. secs. 17 and 18. Va.18*E.
11.00	Trail, SW and NE.
22.50	Enter improvement.
40.00	Left improvement. Set $\frac{1}{4}$ sec. post, from which A B. oak, 4 ins. diam., bears N.8*W., 7 lks. dist. A red fir, 14 ins. diam., bears N.61*E. 21 lks. dist.
40.50	N Umpqua river, 313 lks. wide, runs SW. Distance across river obtained as follows, see diagram.