

40  
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS

7.15 Creek, 20 lks. wide, course NE.

40.46 Set a cedar post, 4 ft. long, 4 ins. diam., 18 ins. in ground, for the  $\frac{1}{4}$  sec. cor. bet. secs. 12 and 13, from which

A fir, 40 ins. diam., bears N.52\*E., 47 lks. dist.  
 " sugar pine, 60 ins. diam., bears S.20\*E., 32 lks. dist.

80.92 To sec. cor.

Land, sloping N., 2d rate.

Timbers, same as last line, 1st class.

January 29, 1879.

GENERAL DESCRIPTION

This section is unsurpassed for fine timbers of the various varieties above named, while the lands South of the river are good second rate. Some rich deposits of gold are found along the river bars, some of which are being very successfully worked; the most extensive of which is located in the NW  $\frac{1}{4}$  of the NE  $\frac{1}{4}$  of the sec. The river is very swift and just below the North line, there are falls of above 10 feet, at which place the Indians have from time immemorial, kept up fisheries.

Subdivisions of T. 26 S., R. 3 W.  
 As surveyed by Sam'l C. Flint, Deputy Surveyor  
 Under contract No. 454, dated June 19, 1882.

Survey commenced July 6, 1882 at the cedar post, 4 ft. long, 4 ins. square, firmly set in the ground, and marked T 26 S Sec. 25 on NE., R 3 W Sec. 36 on SE., S 35 on SW and S 26 on NW faces, with 1 notch on S & E edges; from which

A fir, 12 ins. diam., bears N.50\*E., 6 lks. dist.  
 marked T 26 S R 3 W S 25 B T.

A fir, 20 ins. diam., bears N.30\*W., 32 lks. dist.,