

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS

West, on random, bet. secs. 11 and 14.

Va.19*E.

- 7.00 Spring branch, 2 lks. wide, course NW.
- 35.50 Spring branch, 3 lks. wide, course N.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 51.00 Logging road, course NW)
 72.50 Logging road, course NW.) To Patterson's Saw Mill.
- 80.76 Intersect line, 20 lks. N from cor. to secs. 10, 11, 14 and 15, which is a post, 4 ft. long and 4 ins. sq., marked T 26 S S 11 NE., R 3 W S 14 SE., S 15 SW and S 10 NW, faces with 4 notches on the S and 2 notches on the E edges, from which
- A fir, 16 ins. diam., bears N.72*E., 23 lks. dist., marked T 26 S R 3 W S 11 B T.
- A fir, 30 ins. diam., bears N.46*W., 25 lks. dist., marked S 10 B T.
- A fir, 6 ins. diam., bears S.72*W., 11 lks. dist., marked S 15 B T.
- A maple, 10 ins. diam., bears S.77*E., 19 lks. dist., marked S 14 B T.
- Thence I run
- N.89*51'E., on true line, bet. secs. 11 and 14.
- 40.38 Set maple post, 3 ft. long, 4 ins. sq., firmly in the ground, marked $\frac{1}{4}$ S on N and S faces, from which
- A fir, 36 ins. diam., bears N.10*E., 18 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 36 ins. diam., bears S.70*E., 20 lks. dist., marked $\frac{1}{4}$ S B T.
- 80.76 Cor. to secs. 11, 12, 13 and 14.
- Land, 3d rate, rocky and mountainous.
- Densely covered with forests of fir, cedar, hemlock and pine, and a thick undergrowth of fir, vine maple and huckleberry.

July 8, 1882.