

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 W.

CHAINS	<p>A fir, 20 ins. diam., bears S.55*W., 18 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p>
80.74	<p>Cor. to secs. 14, 15, 22 and 23. Land, 2d rate. Densely covered with forests of fir, cedar, hemlock and laurel and a thick undergrowth of fir, huckleberry and vine maple.</p> <p style="text-align: right;">July 10, 1882.</p>
15.00	<p>Commenced at cor. of secs. 2, 3, 10 and 11 and ran N on random, bet. secs. 2 and 3.</p> <p style="text-align: right;">Va.19*E.</p> <p>Summit of ridge, E and W.</p>
40.00	<p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
79.50	<p>Intersect N bdy. of tp. line, 40 lks. W from cor. to secs. 2, 3, 34 and 35. Made and set new cedar post, 4 ft. long, 4 ins. sq., firmly in the ground, marked T 25 S S 35 NE., R 3 W S 34 NW., T 26 S R 3 W S 2 SE., and S 3 SW, from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N.67*E., 35 lks. dist., marked T 25 S S 35 B T.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S.20*E., 6 lks. dist. marked T 26 S R 3 W S 2 B T.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S.45*W., 10 lks. dist., marked S 3 B T.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N.58*W., 20 lks. dist., marked R 3 W S 34 B T.</p>
40.00	<p>Thence I run S.0*17*W., on true line, bet. secs. 2 and 3.</p> <p>Set laurel post, 3 ft. long, 4 ins. sq., for <math>\frac{1}{4}</math> sec. cor. marked on E and W faces <math>\frac{1}{4}</math> S from which</p> <p style="padding-left: 40px;">A laurel, 4 ins. diam., bears N.45*E., 40 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p>