

Retracement of Boundaries of Sec. 9, T. 26 S., R. 3 W.

CHAINS


Thence
 South, from the sec. cor., retracing bet. secs. 8 and 9.
 40.29 Fall, 250 lks. W of the $\frac{1}{4}$ sec. cor.
 80.70 Fall, 201 lks. W of the cor. of secs. 8, 9, 16 and 17.
 The bearing and length of the north half mile is S.3°33'E.,
 40.37 chs., and of the south half mile is S.0°42'W.,
 40.41 chs.

Dependent Resurvey of Boundaries of Sec. 9,
 T. 26 S., R. 3 W.

The cor. of secs. 8, 9, 16 and 17, is now marked only by
 the old mound of stone, originally built around the
 post.

In the center of the old mound

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
 the ground, for cor. of secs. 8, 9, 16 and 17, with
 brass cap marked



from which

A white oak, 10 ins. diam., bears N.71°E., 82 lks.
 dist., marked T 26 S R 3 W S 9 B T.

A double white oak, 12 ins. diam., bears S.79°E.,
 121 lks. dist., marked T 26 S R 3 W S 16 B T.

A white oak, 12 ins. diam., bears S.33°W., 35 lks.
 dist., marked T 26 S R 3 W S 17 B T.

A white oak, 18 ins. diam., bears N.82°W., 132 lks.
 dist., marked T 26 S R 3 W S 8 B T.

Thence

S.87°25'E., on a true line, bet. secs. 9 and 16.

Along S slope, through timber and undergrowth.