

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Boundaries of Section 9,
T. 26 S., R. 3 W.

CHAINS

- 3.98 Enter flat, bears NE and SW.
- 5.98 Woven wire fence, bears NE and SW ; enter young orchard,
bears same.
- 12.98 Woven wire fence, bears NW and SE; leave young orchard,
bears same.
- 13.98 Enter timber, bears NW and SE.
- 15.98 Old road, bears NE and SW.
- 18.66 Woven wire fence, bears NE and SW.
- 18.95 Glide-Hoaglin road, bears SW and NE.
- 19.13 $\frac{1}{2}$ Proportional measurement.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for W $\frac{1}{16}$ sec. cor., with brass cap marked
- $$\begin{array}{ccc} & & S\ 9 \\ W\ \frac{1}{16} & & S\ 16 \\ & & 1924 \end{array}$$
- from which
- A black oak, 24 ins. diam., bears N.33*E., 13 lks.
dist., marked W $\frac{1}{16}$ S 9 B T.
- A fir, 8 ins. diam., bears S.41*E., 16 lks. dist.,
marked W $\frac{1}{16}$ S 16 B T.
- 20.21 $\frac{1}{2}$ Right bank of North Umpqua River, course SW.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for meander cor. of fractional sec. 9 only, with
brass cap marked
- $$\begin{array}{ccc} T\ 26\ S & & \\ R\ 3\ W & / & M\ C \\ S\ 9 & & \\ & & 1924 \end{array}$$
- from which
- A pine, 34 ins. diam., bears N.16*E., 7 lks. dist.,
marked T 26 S R 3 W S 9 M C B T.
- A fir, 10 ins. diam., bears N.49*W., 43 lks. dist.,
marked T 26 S R 3 W S 9 M C B T.
- 24.96 Left bank of North Umpqua River.