

Dependent Resurvey of Boundaries of Sec. 9,
T. 26 S., R. 3 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for meander cor. of fractional sec. 9 only, with brass cap marked

M C	/	T 26 S
		R 3 W
		S 9
1924		

327500

from which

A fir, 30 ins. diam., bears N.72°E., 46 lks. dist.,
marked T 26 S R 3 W S 9 M C B T.

An ash, 8 ins. diam., bears S.89°E., 33 lks. dist.,
marked T 26 S R 3 W S 9 M C B T.

Ascend NW slope, through timber and undergrowth.

27.69 Point for Angle Point No. 4, Power Reserve, hereinafter described.

28.26 Road, bears NE and SW.

28.59 Rail fence, bears NE. and SW ; enter pasture, bears same.

38.21 Rail fence, bears E and NW.

38.27 The old $\frac{1}{4}$ sec. cor., which is a sound oak post, set by local surveyor; from which

A black oak stump, 36 ins. diam., bears S.24°E.,
318 lks. dist., marked $\frac{1}{4}$ S B T.

A black oak, 32 ins. diam., bears N.56 $\frac{1}{2}$ °W., 366 lks.
dist., shows blaze scars not opened.

Alongside the post, which is on fence line,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	/	S 9
		S 16
1924		

from which

A fir, 20 ins. diam., bears S.85 $\frac{1}{2}$ °E., 179 lks. dist.,
marked $\frac{1}{4}$ S 16 B T.

A white oak, 10 ins. diam., bears N.15°W., 35 lks.
dist., marked $\frac{1}{4}$ S 9 B T.