

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Boundaries of Sec. 9
T. 26 S., R. 3 W.

CHAINS

Thence

S.89*23'E.

Ascend NW slope, along fence.

2.60 Leave fence, turns S.

17.58 Spur, slopes NW; descend NE slope.

17.88 Along NW slope.

20.62 Creek, 2 lks. wide, course NW; ascend NW slope.

30.36 Spur, slopes NE; descend NE slope.

40.17 The point for the cor. of secs. 9, 10, 15 and 16, now marked by a gate post, point verified by reference to the original bearing tree in sec. 15, the only original evidence now found, the other old bearing trees are not found.

Alongside the gate post,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked

| | |
|--------|-------|
| T 26 S | R 3 W |
| S 9 | S 10 |
| S 16 | S 15 |
| 1924 | |

from which

A sugar pine, 36 ins. diam., bears S.85*E., 24 lks. dist., marked B T (the other marks have grown over and I do not uncover them) Old B T.

A fir, 24 ins. diam., bears N.74½*W., 150 lks. dist., marked T 26 S R 3 W S 9 B T New B T.

Trees taken by County Surveyor:

A fir, 32 ins. diam., bears S.8*W., 90 lks. dist., marked C S T 26 S R 3 W S 16 B T.

A fir, 30 ins. diam., bears N.40*W., 93 lks. dist., marked C S T 26 S R 3 W S 9 B T.

No tree available in sec. 10

Land, heavily rolling.