

Dependent Resurvey of Boundaries of Sec. 9
T. 26 S., R. 3 W.

CHAINS

Soil, sandy loam, 1st and 3rd rate.
Timber, fir, pine, oak and alder.
Undergrowth, fir, oak, laurel and hazel.

Thence

N.3*58'W., on a true line, bet. secs. 9 and 10.
Descend NE slope, through timber and undergrowth.

- 6.93 Ascend SE slope.
- 12.67 Ridge, bears NE and SW ; descend NE slope.
- 35.60 Road, bears E and W.
- 37.50 Left bank of North Umpqua River, course NW.
- 41.00 Right bank of river.
- 41.83 The point for the $\frac{1}{4}$ sec. cor., determined by measurement from the original bearing trees, falls on bedrock, on which I mark

$S\ 9\ \overset{\frac{1}{4}}{X}\ S\ 10$

at the exact cor. point; from which

A white oak, 14 ins. diam., bears S.84 $\frac{1}{2}$ *E., 100 lks. dist., old B T face of old blaze decayed, scribe marks show.

A rotted black oak, 12 ins. diam., bears N.54*W., 79 lks. dist., old B T marks rotted away.

A fir, 8 ins. diam., bears N.29*E., 12 lks. dist., marked $\frac{1}{4}$ S 10 B T New B T.

A fir, 14 ins. diam., bears N.63*W., 19 lks. dist., marked $\frac{1}{4}$ S 9 B T New B T.

Thence

N.0*45'E.

- 1.70 Glide-Hoaglin road, bears NW and SE.
- 1.90 Fence, bears NW and SE; enter pasture.
- 3.00 Fence, bears NW and SE; leave pasture; enter plowed field.
- 11.85 Ascend SW slope. Leave plowed field.