

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Boundaries of Sec. 9  
T. 26 S., R. 3 W.

## CHAINS

- 13.20 Fence, bears E and W.
- 26.00 Top of steep ascent; slight ascent on S slope; enter timber and brush, bears E and W.
- 40.04 The point for the cor. of secs. 3, 4, 9 and 10, determined from distance to the original bearing trees, blazes plain, marks overgrown, not opened:
- A black oak, 22 ins. diam., bears N.87\*E., 33 lks. dist.
- A white oak, 18 ins. diam., bears S.34\*E., 75 lks. dist.
- A black oak, 12 ins. diam., bears S.45\*W., 5 lks. dist.
- A black oak, 20 ins. diam., bears N.22\*W., 20 lks. dist.

At the exact cor. point,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T 26 S	R 3 W
S 4	S 3
-----	
S 9	S 10
1924	

from which

- A fir, 10 ins. diam., bears N.58\*E., 71 lks. dist., marked T 26 S R 3 W S 3 B T New B T.
- A black oak, 14 ins. diam., bears S.87\*E., 67 lks. dist., marked T 26 S R 3 W S 10 B T New B T.
- A black oak, 10 ins. diam., bears S.13\*W., 64 lks. dist., marked T 26 S R 3 W S 9 B T New B T.
- A white oak, 5 ins. diam., bears N.24\*W., 2 lks. dist., marked T 26 S R 3 W S 4 B T New B T.

Land, heavily rolling.

Soil, sandy loam, 2nd and 3rd rate.

Timber, fir, pine, oak and laurel.

Undergrowth, laurel, oak, fir and hazel.