

Dependent Resurvey of Boundaries of Sec. 9
T. 26 S., R. 3 W.

CHAINS

Thence

N.89*09'W., on a true line, bet. secs. 4 and 9.

Descend SW slope, through oak openings.

7.50 Ascend SE slope.

9.50 Spur, slopes SE; enter dense undergrowth, bears NW and SE; descend SW slope.

15.80 Draw, course S; ascend SE slope. Enter timber, bears NE and SW.

17.07 Spur, slopes S; descend SW slope.

17.85 Draw, course S; ascend SE slope.

19.25 Spur, slopes S; descend SW slope.

21.13 Creek, 2 lks. wide, course S; ascend NE slope.

21.56 Woven wire fence, bears N and S.

21.78 Woven wire fence, bears NE and SW.

39.06 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S 4
 $\frac{1}{4}$ S 9
1924

from which

A fir, 14 ins. diam., bears N.47*E., 6 lks. dist., marked $\frac{1}{4}$ S 4 B.T.

A fir, 14 ins. diam., bears S.69*W., 29 lks. dist., marked $\frac{1}{4}$ S 9 B T.

48.81 Ridge, bears N and S; descend NW slope.

53.53 Enter flat, bears N and S.

54.96 Rail fence, bears N and S.

62.53 Descend W slope.

78.12 The point for the cor. of secs. 4, 5, 8 and 9, falls at fence cor., from which the original bearing trees:

A dead black oak, 18 ins. diam., bears N.87*E., 270 lks. dist.

A black oak, 20 ins. diam., bears S.80*E., 231 lks. dist.