

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Boundaries of Sec. 9  
T. 26 S., R. 3 W.

CHAINS

A black oak, 20 ins. diam., bears S.34\*W., 329 lks. dist.

A black oak, 18 ins. diam., bears N.50\*W., 340 lks. dist.,

These trees have been opened years ago, face of old blazes decayed, some marks show.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked

T 26 S	R 3 W
S 5	S 4
S 8	S 9
1924	

from which

A fir, 16 ins. diam., bears N.39\*E., 8 lks. dist. marked T 26 S R 3 W S 4 B T.

A fir, 16 ins. diam., bears S.48\*E., 24 lks. dist., marked T 26 S R 3 W S 9 B T.

A fir, 16 ins. diam., bears S.66\*W., 44 lks. dist., marked T 26 S R 3 W S 8 B T.

A fir, 16 ins. diam., bears N.75\*W., 66 lks. dist., marked T 26 S R 3 W S 5 B T.

Land, heavily rolling.

Soil, sandy loam, 2nd rate.

Timber, fir, oak, pine and laurel.

Undergrowth, oak, laurel, hazel, fir and willow.

Thence

S.3\*33'E., on a true line, bet. secs. 8 and 9.

Along W slope, through timber and undergrowth.

7.95 Ascend NW slope.

14.34 Spur, slopes SW; descend SE slope.

20.65 Descend SW slope.