

Dependent Resurvey of Boundaries of Sec. 9  
T. 26 S., R. 3 W.

CHAINS

22.24 Draw, course SW; ascend NW slope.


31.47 Spur, slopes SW; descend S slope.

32.97 Old trail, bears NE and SW.

40.37 The point for the  $\frac{1}{4}$  sec. cor., determined by reference to the original bearing tree, a black oak, 36 ins. diam., which bears N.45\*E., 78 lks. dist., old blaze partly opened, marks visible.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



from which

A fir, 30 ins. diam., bears S.40\*E., 48 lks. dist., marked  $\frac{1}{4}$  S 9 B T.

A fir, 20 ins. diam., bears S.28\*W., 20 lks. dist., marked  $\frac{1}{4}$  S 8 B T.

No trace is found of the old bearing tree in sec. 8.

Thence

S.0\*42\*W.


9.53 Draw, course SE; enter flat, bears same.

18.03 Descend S slope. Leave timber, bears E and W.

19.75 Road, bears NW and SE.

20.20 $\frac{1}{2}$  Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for S  $\frac{1}{16}$  sec. cor., with brass cap marked



from which

A cedar, 28 ins. diam., bears N.14\*E., 48 lks. dist., marked S  $\frac{1}{16}$  S 9 B T.

A black oak, 10 ins. diam., bears N.82-3/4\*W., 183 lks. dist., marked S  $\frac{1}{16}$  S 8 B T.