

## County Surveyor's Record, Douglas County, Oregon


Dependent Resurvey of Boundaries of Sec. 9  
T. 26 S., R. 3 W.

## CHAINS

- 23.42 Across open bench.  
39.42 Descend.  
40.41 The cor. of secs. 8, 9, 16 and 17.

Land, heavily rolling.  
Soil, sandy loam, 2nd rate.  
Timber, fir, pine, oak and laurel.  
Undergrowth, hazel and fir.

## Subdivision of Sec. 9, T. 26 S., R. 3 W.

- From the  $\frac{1}{4}$  sec. cor. of sec. 9 and 16.  
N.0°51'W., calculated bearing, on a random line on meridional center subdivisional line of sec. 9.
- 13.00 Left bank of North Umpqua River. Set temp. special meander cor.
- To make a triangulation across the river, I designate the above temp. cor. point A and set a flag B at point for temp. special meander cor. on right bank of river.
- From point A, auxiliary flag bears N.49°15'W; from point B auxiliary flag bears S.46°18'W., 3.71 chs.
- 
- dist. All bearings checked by direct reading of the solar and all angles checked by deflection. Dist. across river 4.94 chs.
- 17.94 Right bank of river. Set temp. special meander cor.  
20.86 Calculated dist. Set temp. 1/16 sec. cor.  
41.73 Calculated dist. Set temp. center  $\frac{1}{4}$  sec. cor.  
81.76 Fall 12 lks. E of the  $\frac{1}{4}$  sec. cor. bet. secs. 4 and 9.

From the  $\frac{1}{4}$  sec. cor. bet. secs. 9 and 10.

N.89°20'W., calculated bearing, on a random line, on latitudinal center subdivisional line of sec. 9.

To avoid bend of North Umpqua River, I offset North, 1.95