

Subdivisions of Sec. 9, T. 26 S., R. 3 W.

CHAINS

chs.; thence on traverse line along road,

N.64 $\frac{1}{4}$ \*W., 8.89 chs.

N.85-3/4\*W., 5.97 chs.

S.83 $\frac{1}{2}$ \*W., 3.43 chs.

S.58\*W., 4.42 chs.

S.40 $\frac{1}{2}$ \*W., 4.91 chs. thence offset

North 0.48 chs. to random line.

38.01 Intersect random meridional center line of sec. 9, 12 lks. S of temp. center  $\frac{1}{4}$  sec. cor.

56.60 Calculated dist. Set temp. 1/16 sec. cor.

75.37 Fall 7 lks. S of the  $\frac{1}{4}$  sec. cor. bet. secs. 8 and 9.

From the  $\frac{1}{4}$  sec. cor. bet. secs. 8 and 9.

S.89\*17'E., on true latitudinal center line of sec. 9.

Over rolling land, through heavy timber and dense undergrowth.

Descend along SE slope.

7.35 Draw, course SW; ascend SW slope.


11.00 Spur, slopes SW.

11.60 Draw, course SW.

13.80 Enter opening, bears N and S.

17.60 Enter timber, bears N and S.

18.65 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for west center 1/16 sec. cor. of sec. 9, with brass cap marked



S 9  
1924

from which

An ash, 14 ins. diam., bears N.21\*E., 13 lks. dist.,

marked C W 1/16 S 9 B T.

A fir, 9 ins. diam., bears S.52\*W., 14 lks. dist.,

marked C W 1/16 S 9 B T.