

Subdivisions of Sec. 9, T. 26 S., R. 3 W.

CHAINS

- 23.40 Spur, slopes SW; descend SE slope.
 28.90 Woven wire fence, bears NW and SE.
 37.30 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for center $\frac{1}{4}$ sec. cor. of sec. 9, with brass cap marked

$$C \frac{1}{4} S 9$$

$$1924$$

from which

A white oak, 7 ins. diam., bears S.16°E., 7 lks. dist., marked C $\frac{1}{4}$ S 9 B T.

A black oak, 8 ins. diam., bears N.47°W., 8 lks. dist., marked C $\frac{1}{4}$ S 9 B T.

Land, rolling.

Soil, clay loam, 2nd and 3rd rate.

Timber, fir, pine, oak, laurel and cedar.

Undergrowth, fir, oak, hazel and vine maple.

From the center $\frac{1}{4}$ sec. cor.

S.0°56'E., on true meridional center subdivisional line of sec. 9.

Descend SE slope, through scattering timber and undergrowth.

- 6.90 Woven wire fence, bears E and W.
 14.00 Fence, bears E and W; foot of descent; thence level.
 20.82 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for south center $\frac{1}{16}$ sec. cor. of sec. 9, with brass cap marked

$$S \frac{1}{16} \begin{array}{c} C \\ | \\ S 9 \\ | \\ C \end{array}$$

$$1924$$

from which

A cedar, 20 ins. diam., bears N.50°E., 8 lks. dist., marked S $\frac{1}{16}$ S 9 B T.