

Subdivisions of Sec. 9, T. 26 S., R. 3 W.

CHAINS

A fir, 6 ins. diam., bears S.0°30'W., 44 lks. dist.,  
marked S 1/16 S 9 B T.


21.63 Point for angle point No. 1, Power Reserve, hereinafter described.

21.82 Wire fence, bears NE and SW.

22.00 Glide-Hoaglin road, bears NE and SW.

23.70 Right bank of North Umpqua River.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for special meander cor., with brass cap marked



S M C  
1924

*3405-1*


from which

A fir, 8 ins. diam., bears S.83°W., 57 lks. dist.,  
marked S 9 S M C B T.

A fir, 18 ins. diam., bears N.9°W., 51 lks. dist.,  
marked S 9 S M C B T.

28.64 Left bank of river.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for special meander cor. of sec. 9, with brass cap marked



1924

*3405-1*

from which

An ash, 11 ins. diam., bears South, 24 lks. dist.,  
marked S 9 S M C B T.

A dogwood, 7 ins. diam., bears S.48½°W., 33 lks. dist., marked S 9 S M C B T.

Ascend NW slope, through heavy timber and dense undergrowth.