

Subdivisions of the Southwest Quarter of Sec. 9,
T. 26 S., R. 3 W.

CHAINS

20.53 $\frac{1}{2}$ Intersect SW $\frac{1}{4}$ latitudinal line. At the point of inter-
section

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for SW $\frac{1}{16}$ sec. cor. of sec. 9, with brass
cap marked

SW $\frac{1}{16}$ S 9
1924

from which

A cedar, 7 ins. diam., bears S.55*E., 12 lks. dist.,
marked S W $\frac{1}{16}$ S 9 B T.

A black oak, 12 ins. diam., bears N.2*W., 25 lks.
dist., marked S W $\frac{1}{16}$ S 9 B T.

28.98 Ascend S slope.

41.07 The west center $\frac{1}{16}$ sec. cor. of sec. 9.

From the South $\frac{1}{16}$ sec. cor. bet. secs. 8 and 9.
S.88*19'E., on a true line, through the center of the SW
 $\frac{1}{4}$ of sec. 9.

Along rolling S slope, through timber and undergrowth.

4.98 Draw, course S.

18.88 Intersect the SW $\frac{1}{16}$ sec. cor. of sec. 9.

26.86 Barbed wire fence, bears NE and SW.

Leave timber; enter opening, bears NE and SW.

37.76 The south center $\frac{1}{16}$ sec. cor. of sec. 9.

Land, rolling.

Soil, sandy loam, 2nd and 3rd rate.

Timber, fir, pine, oak and laurel.

Undergrowth, oak, laurel, hazel and fir.

Meanders in SW $\frac{1}{4}$ Sec. 9, T. 26 S., R. 3 W.

Meanders of the right bank of North Umpqua River, up
stream.