

7v

County Surveyor's Record, Douglas County, Oregon

Meanders in the Southwest Quarter of sec. 9,
T. 26 S., R. 3 W.

CHAINS

Commence at the meander cor. of frac. sec. 9 only, on the right bank of the North Umpqua River.

Thence with meanders in SE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 9.

N.46°11'E., 24.70 chs. To special meander cor. of frac. E and W halves of Sec. 9.

Meanders of the left bank of North Umpqua River, down stream.

Commence at the special meander cor. of frac. E and W halves of sec. 9, on the left bank of the river.

Thence with meanders in SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 9.

S.45°40'W., 10.90 chs.

S.22°00'W., 2.20 chs.

S.58°50'W., 5.24 chs. To meander cor. of frac. sec. 9 only.

Land, level.

Soil, sandy loam, 1st rate.

Timber, alder and maple.

Undergrowth, vine maple and hazel.

Segregation Survey of Power Reserve in SE $\frac{1}{4}$ SW $\frac{1}{4}$
Sec. 9, T. 26 S., R. 3 W.

I commence at Angle Point No. 1, which is on the meridional center subdivisional line of Sec. 9, 0.81 chs. S.0°56'E., of the South center 1/16 sec. cor. and 2.07 chs. (100 ft. normal dist. from the meander line), N.0°56'W of the special meander cor. bet. frac. E and W halves of sec. 9, on the right bank of the North Umpqua River. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for Angle Point No. 1, Power Reserve, with brass cap marked

AP 1
P R
1924