

West Boundary of T. 26 S., R. 4 W., W. M. as surveyed by James E. Freeman, Deputy Surveyor, under Contract No. 1, dated May 28, 1851.

CHAINS	
	South, on W. bdy. of sec. 6. Var. 19*E.
20.11	Top of hill, course SW.
22.00	Commence descending hill.
40.00	Set $\frac{1}{4}$ sec. post. Deposit 2 quarts stone and raise mound with trench as per instruction.
60.00	Descend to bottom of hill in head of ravine, bears E.
77.00	Ascend to top of hill.
79.90	Begin to descend.
80.00	Set post cor. of secs. 1, 6, 7 and 12. Planted 4 stones 3x4 ins., and raised mound, from which A B. oak, 24 ins. diam., bears S.63*E., 565 lks. dist. A B. oak, 18 ins. diam., bears S.51*E., 545 lks. dist. Land, hilly. Timber, a few scattering trees. Soil, 2nd rate, clay loam.
	South, on the W. bdy. of sec. 7. Var. 19*45'E.
40.00	Set $\frac{1}{4}$ sec. post, from which A Y. pine, 36 ins. diam., bears N.28*E., 84 lks. dist. A W. oak, 9 ins. diam., bears S.30*W., 300 lks. dist.
61.00	Var. 16 $\frac{1}{2}$ *E.
61.00	Set post, witness cor. to secs. 7, 12, 13 and 18, on the brow of a bluff, descends SE. to Umpqua river. A Laurel, 12 ins. diam., bears N.16*E., 1 lks. dist. A Laurel, 8 ins. diam., bears N.33*W., 1 lks. dist. West, 8 chs., base. Thence, South 2 chs. Object in line bears S.11*E. 43 chs., 18 lks. dist.
80.00	Sec. cor. is inaccessible. The river bluff, is W. of cor. and extends in the form of a crescent from one witness cor. to the other. Land, hilly. Timber, a few scattering trees.