

County Surveyor's Record, Douglas County, Oregon


Subdivisions and Meanders of Umpqua river in Township 26 S.,
R. 4 W., W. M.

CHAINS

53.00 Observed distance across river to tree.
54.30 Set meander stake on south or left bank of Umpqua River,
from which,

An Ash, 6 ins. dia., bears S.76*W., 32 lks. dist.

An Ash, 6 ins. dia., bears S.79*E., 20 lks. dist.



Distance across river obtained as follows, viz.

Caused a flag to be set on line on north side of river at A, the same being 130 lks. from meander post.

Measured B.C.=200 lks.

Constructed DCB & ABD=right angles & Measured CD=77 lks, then by similarity of triangles, we have.

$$77 : 200 :: 200 : 519$$

$$519 - 130 = 389 = \text{Width of river.}$$

58.19 To north or right bank of Umpqua river, on which set
meander post, from which,

A B. Oak, 3 ins. dia., bears S.68*W., 74 lks. dist.

An Ash, 4 ins. dia., bears S.75*E., 45 lks. dist.

80.00 Set post corner of Secs. 16, 17, 8 & 9, from which,

A W. Oak, 15 ins. dia., bears N.82*E., 187 lks. dis.

A W. Oak, 23 ins. dia., bears S.68*E., 237 lks. dis.

A W. Oak, 10 ins. dia., bears S.28*W., 328 lks. dis.

(no trees convenient N. W.)

Land, 2nd rate, with some first rate prairie, near river.

Timber, oak & pine.

East, on random between Secs. 9 & 16.

40.00 Set temporary $\frac{1}{4}$ Sec. post.

79.75 Intersect N. & S. line, 30 lks. South of post corner of
Secs. 9, 10, 15 & 16, from which corner I run,
S.89*47'W., on true line between Secs. 9, & 16.

39.87 $\frac{1}{2}$ Set $\frac{1}{4}$ Sec. post from which,

A B. Oak, 15 ins. dia., bears S.68*W., 277 lks. dist.

A W. Oak, 5 ins. dia., bears N.25*E., 183 lks. dist.

79.75 To post corner of Secs. 8, 9, 16 & 17.

Land 2nd rate.

Timber, pine & oak.