

Sub-divisions of T. 26 S., R. 5 W.

CHAINS

. bears N.63*E. Distance to flag, 395 lks. Thence measured West 99 lks. and

3.42 Set temporary Meander post on right bank.

Course of River S.10*E. Bank low and brushy.

Var.18*25'E.

50.00 Intersect right bank of river and set temp. post. Thence offset North 500 lks. Thence N.89*43'W. 34.93 chs. Thence South 380 lks to Meander post 108 lks. North of Sec. Cor.(in river). Therefore the intersection will be

84.93 Intersect N.&S. line 12 lks. S. of Sec. Cor. S.89*38'E. on true line between Secs. 19 & 30.

34.90 Leave river and set Meander post, from which

A Y. Oak 14 ins. diam. bears N.37*W.22 lks.

A Y. Oak 12 ins. diam. bears S.74*E. 65 lks.

Course of river N.85*W. Bank 20 feet high.

39.43 Enter field N.15*E.&S.15*W.

44.00 Leave field N.75*W.&S.75*E.

44.93 Set $\frac{1}{4}$ Sec. post, from which

A Y. Oak 36 ins. diam. bears N.76 $\frac{3}{4}$ *E. 327 lks.

A Pine. 36 ins. diam. bears S.78 $\frac{1}{4}$ *E. 518 lks.

Var.20*00'E.

A road N.75*W.&S.75*E.

81.51 Set Meander post on right bank Umpqua, from which

An Ash 12 ins. diam. bears S.65*W. 28 lks.

An Ash 12 ins. diam. bears N.50*W. 31 lks.

84.93 To Section Corner (in river)

West 35 and East 3 chains in river, balance rolling

Oak Openings.

Soil, 2nd rate.

North, between Secs. 19 & 20

From Meander post between Secs. 20 & 29 measured N.20*W.