

County Surveyor's Record, Douglas County, Oregon

Survey of the Sub-divisions and Meanders of T.26S., R.6 W.
as surveyed by Henry S. Gile, Deputy Surveyor, under contract
No. 31, dated April 7, 1853.

CHAINS		
	North, between Sec. 35 and 36.	
		Var.17*50'E.
10.00	Top of hill, course N.70*E.&S.70*W.	-150
20.00	A Ravine and spring, course N.E.	-200
24.00	Leave fir timber and enter oak openings, course N.E.&S.W.	+30
40.00	Set $\frac{1}{2}$ sec. post, from which	+75
	A Y. Oak 36 ins. diam. bears N.74 $\frac{1}{2}$ *W. 80 lks.	
	A W. Oak 12 ins. diam. bears S.20 $\frac{1}{2}$ *E. 170 lks.	
		Var.17*30'E.
49.09		Var.20*50'E.
51.00	Top of hill, course N.70*E.&S.70*W.	+150
80.00	Set post cor. to Secs. 25,26,35&36, from which	-60
	A Y. Oak 14 ins. diam. bears N.28*W. 7 lks.	
	A Y. Oak 14 ins. diam. bears N.5*E. 48 lks.	
	A Laurel 24 ins. diam. bears S.55*E. 90 lks.	
	A Laurel 7 ins. diam. bears S.43 $\frac{1}{2}$ *W. 17 lks.	
	South 24 chs. timbered with fir, laurel, oak, North	
	54 chs. Oak openings.	
	Soil, all 2nd rate.	
	East, on random between Secs. 25 & 36.	
		Var.18*15'E.
79.60	Intersect North and South lines 3 lks. South of Section corner.	
	S.89*59'W. On true line between Secs. 25 & 36.	
	The N.E. corner of Gen. Jo. Lanes claim bears S.53 $\frac{3}{4}$ *W.	
8.50	Road to Mines, course N.&S.	level
20.84	The above corner bears S.10 $\frac{3}{4}$ *W.	level
21.50	Bed of Stream, 5 lks. wide, course South	level
30.00	Leave prairie and begin to ascend Oak hilly course N.&S.	+10