

46

Survey of the Sub-divisions and Meanders of T. 26 S., R. 6 W.

CHAINS		
60.00	A trail at foot of hill, course N.E.&S.W.	-200
66.00	Bed of stream 10 lks wide, course S.W. (dry)	-5
80.24	To Section Corner	+100
	East 43 chs. hilly oak openings.	
	West 37 chs. thinly timbered with oak with a dense undergrowth of oak, hazel, laurel and fern.	
	Soil, all 3rd rate.	
	N.89°46'W. on random between Secs. 7 & 18.	
	Var 18°30'E.	
56.40	Intersect right bank of Umpqua River and set temp. Meander post. Measured S.16½°E. 348 lks base. Thence over river into line on left bank whence flag bears S.67½°E. Distance over river 710 lks., thence	
62.57	East 93 lks. and set temp Meander post.	
79.50	Intersect West boundary 36 lks S. of section corner. S.89°31'E. on true line between Secs. 7 & 18.	
8.00	Foot of hill, course N.30°E.&S.30°W.	-80
15.00	A slough 60 lks. wide, North (dry)	
16.90	Intersect left bank of Umpqua river and set Meander post, from which	
	An Ash 10. ins. diam. bears N.4½°W. 150 lks.	
	A Y. Oak 22 ins. diam. bears S.50°W. 51 lks.	
	Course of river, North. Bank, 15 feet high, current rapid and deep. Bed, Rocky.	
24.69	Set Meander post on right bank, whence	
	A W.Oak 6 ins. diam. bears N.1½°W. 80 Lks.	
	An Ash 4 ins. diam. bears S.65°E. 4 lks.	
29.00	Leave low brushy bottom and enter oak openings, Course East and West	+10
39.50	Set ¼ Sec. post, from which	+150
	A Y. Oak 18 ins. diam. bears N.34°E. 58 lks.	
	A ditto 15 ins. diam. bears S.54½°W. 52 lks.	