Survey of Sub-divisions and Meanders of T. 26 S., R. 6 W.

CHAINS		
70.50	Leave low rocky bottom and enter Oak openings, Course N.E.&S.W.	+10
80.00	Set post cor. to Secs. 5,6,7, & 8, from which	
	A Y. Oak 36 ins. diam. bears S.73½°W. 580 lks.	
	A ditto 36 ihs. diam. bears N.41¾°W.382 lks.	
	A W. Oak 14 ins. diam. bears N.60¼°E. 594 Lks.	
	A ditto 24 ins. diam. bears S.89°E. 295 lks.	
	South 30 chs. hilly and bushy with scattering oak timber. Soil, 3rd rate.	
	Balance, prairie oak openings, soil 2nd rate.	
	S.89°44'E. On random between Secs. 5 & 8. Var.18°15'E.	
21.66	Intersect left bank of Umpqua river and set Temp. Meander post.	
22.71	Set a flag on rocky,bar, thence over river into line and measured South 190 lks base, whence flag bears N.66½°W. Distance over river 437 lks.	
27.08	Set temp. meander post.	
80.48	Intersect N.&S. line 15 lks. South of Section Corner. N.89°50'W. on true line between Secs. 5 & 8.	
12.50	Top of hill, course N.&S.	+250
25.50	A Ravine, course S.E. Enter Brush N.W.&S.E.	-350
40.24	Set ¼ sec. post, from which	+500
	A. W. Oak 6 ins. diam. bears N.9°E. 86 lks.	
	A Y. Oak 9 ins. diam. bears S.40°W. 89 lks.	
	Leave brush and enter oak openings, course N. & S, top of hill N.&S.	
53.25	A trail, course N.&S.	-600
53.40	Intersect right bank of Umpqua river and set Meander post, from which	
	A Y. Oak 6 ins. diam. bears S.21°W. 31 lks.	
	A ditto 30 ins. diam. bears N.2¼° E. 89 lks.	
	Course of river N.30°W., bank 10 feet high and rocky. Bed rocky and current rapid.	