

County Surveyor's Record, Douglas County, Oregon

4575

49

Survey of Sub-divisions and Meanders of T. 26 S., R. 6 W.

CHAINS		
58.92	Set Meander post on left bank, whence A Pine 9 ins. diam. bears S.63*W. 76 lks. A Y. Oak 18 ins. diam. bears N.23 $\frac{1}{4}$ *W. 188 lks.	
74.50	I leave low gravelly bottom and enter oak openings, course N.20*E.&S.20*W.	level level
80.48	To Section Corner East of river hilly oak openings and brushy timber. Soil, 3rd rate. West of river gravelly bottom and oak openings. Soil, 2nd and 3rd rate.	
N.89*31'W. on random between secs. 6 & 7. Var. 18*15'E.		
79.64	Intersect West boundary 46 lks North of Section Corner. S.89*50'E. on true line between Secs. 6 & 7.	
28.00	Top of hill, course N.30*E.&S.30*W.	+350
39.69	Set $\frac{1}{4}$ sec. post, from which A W. Oak 20 ins. diam. bears N.60*W. 156 lks. A ditto 16 ins. diam. bears S.82*E. 182 lks. Var.18*30'E.	-200
50.00	Top of hill, course N.&S.	+200
65.00	Foot of hill, course N.&S.	-50
79.64	To Section Corner Land, principally Oak openings, Soil, 3rd rate.	-10
North, on random between secs. 5 & 6 Var.18*15'E.		
34.89	Intersect left bank of Umpqua River and set temp. Meander post.	
37.44	Set a flag at water edge, thence over river to, a point East of flag, thence North 787 lks, thence	