

County Surveyor's Record, Douglas County, Oregon

-/-

West Boundary of T. 26 S., R. 7 W., W.M.
 as surveyed by Dennis Hathorn, Deputy Surveyor
 under Contract No. 57, dated April 12, 1855.

CHAINS		
	South on W. boundary of Sec. 6.	
	Va. 19½*	
9.00	A branch, 2 lks. wide, course W.	+30
11.75	A summit of ridge, course E. and W.	+40
13.25	A branch, 2 lks. wide, course SW.	-25
31.25	A summit of ridge, course E and W.	+150
40.00	Set ¼ sec. post from which	+50
	A Hemlock, 12 ins. diam., bears N.45*W., 14 lks. dist.	
	A Hemlock, 20 ins. diam., bears N.85*E., 14 lks. dist.	
67.95	A branch, 3 lks. wide, course W.	+20
80.00	Set post, cor. secs. 6, 7, 1 and 12 from which	+50
	A Fir, 48 ins. diam., bears N. 40*E., 38 lks. dist.	
	A Fir, 24 ins. diam., bears S. 20*E., 64 lks. dist.	
	A Fir, 20 ins. diam., bears S.40*W., 40 lks. dist.	
	A Cedar, 30 ins. diam., bears N.25*W., 41 lks. dist.	
	Land, uneven,	
	Soil, 3rd rate.	
	Timber, fir, cedar, hemlock, laurel etc.	
	June 12, 1855	
<hr/>		
	South on W. boundary of sec. 7	
	Va. 19½*	
4.00	Commence descending	+10
9.90	Set flag on edge of rocks, from point in	100
	line South, offset E. 110 lks. base, whence flag	
	bears N.29*W., 200 lks. dist.	
10.60	A branch, 5 lks. wide, course W.	-60
24.00	A creek, 25 lks. wide, course NW.	-75
40.00	Set ¼ sec. post from which	+400
	A laurel, 12 ins. diam., bears N.42*W., 15 lks. dist.	
	A Fir, 30 ins. diam., bears S.10*E., 27 lks. dist.	
64.00	East end of ridge	+300
66.65	Perpendicular rocks. Offset W.	-50
	2 chs. and S. 4 chs., Thence to line	
80.00	Marked a fir, 15 ins. diam., for cor. secs. 7, 18, 12	
	and 13, from which	-100