

County Surveyor's Record, Douglas County, Oregon

- 25 -

Subdivisions of T. 26 W., R. 7 W., W.M.

CHAINS

40.00	Set temp. $\frac{1}{2}$ sec. post.	
79.34	Intersect N. and S. line, 14 lks. S. of cor. S.89*54'W. On true line between secs. 10 and 15	
23.25	Enter fir timber, course E. and W.	+40
39.67	Set $\frac{1}{2}$ sec. post, from which A fir, 12 ins. diam., bears N.9*E., 60 lks. dist. A fir, 12 ins. diam., bears S.75*W., 44 lks. dist.	+30
58.60	Branch, 2 lks. wide, course N.	-10
79.34	To section corner. Land, hilly Timber, fir, and oak. Soil, 3rd rate.	+60
North, bet. secs. 9 and 10. Va. 19 $\frac{1}{2}$ *E.		
22.00	Branch, 2 lks. wide, course NW.	-150
35.50	Branch, 5 lks. wide, course N.	-20
36.00	Leave same, course NE.	- 2
36.80	Same, course NW.	- 4
40.00	Set $\frac{1}{2}$ sec. post, from which A fir, 6 ins. diam., bears S.88*E., 15 lks. dist. A Cedar, 10 ins. diam., bears S.67*W., 26 lks. dist.	+ 4
40.75	Branch, 3 lks. wide, course NE.	- 5
43.80	Same, course NW.	- 4
49.00	Branch, 1 lk. wide, course W.	- 6
63.76	A fir, 30 ins. diam.	-4
80.00	Set post cor. secs. 3, 4, 9 and 10, from which A hemlock, 10 ins. diam., bears S.4*W., 25 lks. dist. A Hemlock, 12 ins. diam., bears N.13*E., 20 lks. dist. A Hemlock, 6 ins. diam., bears S.35*E., 45 lks. dist. A fir, 8 ins. diam., bears N.75*W., 31 lks. dist. Land, about as last mile, Timber, fir, hemlock, cedar and yew.	-15