

County Surveyor's Record, Douglas County, Oregon

-45-


Subdivisions of T. 26 S., R. 7 W., W.M.

CHAINS

East on random bet. secs. 20 and 29.

Va. $19\frac{1}{2}^{\circ}$ E.

10.00 Perpendicular bluff rocks, 200 ft. high. Distance to opposite side of creek by tri-angulation = 9.09. Measured base of 100 lks. at right angle to line then 11 lks:100::100:x



A B C & A C D being similar right-angle triangles. A B (11) : BC (100)

to BD.

19.09 (x) = 909 lks. (9.09 in old book)

40.00 Set temporary $\frac{1}{4}$ sec. post.

49.50 Stream, 8 lks. wide, course NW.

70.25 Stream, 10 lks. wide, course NW.

80.30 Intersect line, 90 lks. south of corner to secs. 20, 21, 28 and 29. Thence, I ran S.89°21'W. on true line between secs. 20 and 29.

40.15 Set a Laurel post for $\frac{1}{4}$ sec. cor., from which a Ghinquapin, 6 ins. diam., bears N.65°W., 15 lks. dist. A Laurel, 7 ins. diam., bears S.50°E., 10 lks. dist.

80.30 Corner to secs. 19, 20, 29 and 30.

Land, 3rd rate,

Timber, Fir, Hemlock, Cedar, Laurel and Maple.

Undergrowth as usual.

West on random between Secs. 19 and 30

Va. $19\frac{1}{2}^{\circ}$ E.40.00 Set temp. $\frac{1}{4}$ post.

60.30 Stream, 8 lks. course NE.

80.00 Stream, 3 lks., course NE.

80.80 Intersected line, 10 lks. north from cor. to secs. 19, 30, 24 and 25. Thence I ran, N.89°56'E. on true line between Secs. 19 and 30.

40.80 Set Cedar post for $\frac{1}{4}$ sec. cor., 3 ft. long and 4 ins. sq., firmly in the ground, from which,