County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26, S., R. 7 W., W.M.

CHAINS	
	West on random bet. secs. 7 and 18 Va. 19½°E.
8.50	Stream, 3 lks. wide, course North.
40.00	Set temp. ¼ post.
68.00	Hubbard Creek, 25 lks. wide, course North.
80.70	Intersect line, 75 lks. south of corner to secs. 7 and 18, 12 and 13. Thence I ran,
	S.89°28'E., on true line bet. Secs. 7 and 18.
40.70	Set a Fir post for ¼ sec. cor, 3 ft. long and 4 ins. sq., from which,
	A Fir, 36 ins. diam., bears S.25°W., 31 lks. dist.
	A Hemlock, 6 ins. diam., bears N.15°W., 30 lks. dist.
80.70	Corner to secs. 7, 8, 17 and 18.
	Land, 3rd rate, high spurs, and deep canyons.
	Timber, Hemlock, Fir, Cedar, Laurel, Maple.
	Undergrowth, Fir, Laurel, Hazel and Vine-maple.
	North on true line bet. secs. 7 and 8 Va. 19½°E.
5.10	Stream, 5 lks. wide, course West.
12.25	Stream, 8 lks. wide, course West.
40.00	Set Cedar post for ¼ sec. cor, 3 ft. long and 3 ins. sq., from which,
	A Fir, 8 ins. diam., bears S.60°E., 23 lks. dist.
	A Cedar, 36 ins. diam., bears S.65°W., 57 lks. dist.
45.00	Summit of ridge, E. and W.
75.50	Stream, 2 lks. wide, course S.75°W.
80.00	Corner to secs. 5, 6, 7 and 8, at which I set a Hemlock post, 40 ins. long and 4 ins. sq., from which
	A Fir, 15 ins. diam., bears N.20°W., 85 lks. dist.
	A Fir, 15 ins. diam., bears N.20°E., 66 lks, dist.
	A Fir, 24 ins. diam., bears S.80°W., 14 lks. dist.
	A Fir, 16 ins. diam., bears S.85°E., 18 lks. dist.