

## Subdivisions, of T. 26 S., R. 8 W.

CHAINS  
40.10 $\frac{1}{4}$  sec. cor. 8 lks. West.

59.50 Summit of ridge, bears NE. and SW. and descend.

74.65 A stream, 3 lks. wide, course NW.

80.13 Intersect 18 lks. E. of the cor. of secs. 25, 30, 31, and 36, marked and witnessed as described by the Surveyor General, trees and post in good condition. The bearing of this line is therefore N.0\*8'W.

Returning to the SE. cor. of T 26 S R 8 W heretofore described I run thence

West, to retrace S. bdy. of sec. 36.

Va.20\*15'E.

Descend from cor.

26.60 A stream, 3 lks. wide, course NW.

36.80 A stream, 2 lks. wide, course NW.

39.97  $\frac{1}{4}$  sec. cor. 3 lks. S., witness trees in good condition and as described by the Surveyor General.

44.45 A stream, 10 lks. wide, course SW.

49.40 A stream 5 lks. wide, course S.

80.20 Intersect at cor. of secs. 1, 2, <sup>35</sup>25, and 36, which is a hemlock marked and witnessed as described by the Surveyor General.

Consequently the S. bdy. of sec. 36 bears W.

Therefore the bearings are as stated by the Surveyor General and my chaining practically agrees with field notes furnished by the Surveyor General of the original survey.

Set. 14, 1896.

I commenced at the cor. of secs. 1, 2, 35, and 36 on the S. bdy. of the Tp. heretofore described. Thence I run N.0\*1'W. bet. secs. 35 and 36.

Va.20\*15'E.

2.50 Spring branch, course SE. ascend.

10.50 A fir, 48 ins. diam., on line. I mark 2 notches on N. and S. sides.

19.00 A fir, 40 ins. diam. on line. I mark 2 notches on N. and S. sides.