

Corrections of Surveys in T. 26 S., R. 8 W.
Same Deputies and Contract,

CHAINS	<p>boundaries of the first tier of Secs. where ever necessary correct the markings thereon to correspond with the notes thereof on file, in the U.S. Surveyor General's Office, and verify the witnesses to each.</p> <p>From the Cor. of Secs. 2, 3, 34, and 35 on the South boundary of the Township and run thence N.0*2'W. bet. secs. 34 and 35, tracing and re-measuring original line.</p>
40.00	<p>The $\frac{1}{4}$ Sec. Cor. as described in original notes.</p>
80.00	<p>The Cor. to secs. 26, 27, 34 and 35, as described by the Examiner, I inscribe the omitted markings thereon Viz: T 26 S on NE, R 8 W on SE. and 1 notch on S. and 2 notches on E. edges; dig pits 18x18x12 ins. in each Sec. 5$\frac{1}{2}$ ft. distant and raised mound of earth 4 ft. base, 2 ft. high, W. of Cor.</p> <p>Thence</p> <p>N.89*51'E. bet secs. 26 and 35, tracing without re-measuring to the $\frac{1}{4}$ Sec. Cor. which I find as reported in the notes now on file in the U.S. Surveyor General's Office.</p> <p>From the corner of Secs. 26, 27, 34 and 35, I run N.0*2' W. bet. Secs. 26 and 27 tracing and remeasuring original line.</p>
40.00	<p>The $\frac{1}{4}$ Sec. Cor. as reported in original notes. I dig pit 18x18x12 ins. 3 ft. N. of post and erase markings on NW. witness tree.</p>
	<p>The bearing and distance to the NE. witness tree is as reported by the Examiner, to wit: N.2*30'E., 219 lks. dist.</p>
80.00	<p>The Cor. to Secs. 22, 23, 26 and 27, I found marked as described by the Examiner and the witness trees destroyed by fire. I supply omitted markings thus: T 26 S on NE, R 8 W on SE, and 2 notches on S. and E. edges. dug pits 18x18x12 ins. in Secs. 23, 26 and 27, 5$\frac{1}{2}$ ft. distance and raised mound of earth, 4 ft. base, 2 ft. high W. of Cor. The bearing tree in Sec. 22 as</p>