

## Corrections of Surveys in T. 26 S., R. 8 W.

## CHAINS

originally reported. The other witness trees were destroyed by fire.

From the Cor. of Secs. 22, 23, 26 and 27, I trace without remeasuring the surveyed lines and examine each cor. on the W. and N. boundaries of the remainder of this tier of secs. verified the witnesses thereto and where necessary corrected the markings thereon to correspond with the notes thereof on file in the U.S. Surveyor General's Office.

I now go to the Cor. of Secs. 3, 4, 33, and 34, on the S. bdy. of the Tp. and as there is a considerable difference reported bet. my measurement and that of the Examiner on the line bet. Sec. 33 and 34, I therefore remeasure it as follows.

N.0\*2'W. bet. secs. 33 and 34.

40.07 Intersect  $\frac{1}{4}$  Sec. Cor. I find the distance to the NE. bearing tree to this cor. as reported by the Examiner to Wit: 115 lks. dist. instead of 15 lks. as reported in the notes now on file in the U. S. Surveyor General's Office.

80.11 Intersect Cor. to Secs. 27, 28, 33 and 34, marked as reported by the Examiner. I erase the Roman and mark with Arabic figures to wit: T 26 S S 27 on NE, R 8 W S 34 on SE, S 33 on SW, and S 28 on NW. faces, with one notch on S. and 3 notches on E. edges, from which the witness trees are as reported in original notes. I find the SW. bearing tree which the Examiner failed to find, Viz: A fir, 40 ins. in diam., bears S.14\*W., 134 lks. dist.  
Thence

N.89\*52'E. bet secs. 27 and 34 remeasuring.

39.97 Intersect  $\frac{1}{4}$  Sec. Cor. which I found marked  $\frac{1}{4}$ S. on S. face as described by the Examiner. I erase the markings on S. and mark  $\frac{1}{4}$  S on N face as described in original notes.

80.03 Intersect Cor. to Secs. 26, 27, 34 and 35.

From the Cor. of Secs. 27, 28, 33, and 34, I run