

Corrections of Surveys in T. 26 S., R. 8 W.

CHAINS	N.0*2'W. bet. secs. 27 and 28 remeasuring.
40.00	The $\frac{1}{4}$ sec. cor. as described in original notes.
80.00	The Sec. Cor. to Secs. 21, 22, 27, and 28 is found as described by the Examiner. I supply the omitted markings as follows: T 26 S on NE, R 8 W on SE. and 2 notches on S. and 3 notches on E. edges, from which the bearing trees are as originally recorded. Thence N.89*48'E. bet. secs. 22 and 27 tracing and remeasuring to
39.93	The $\frac{1}{4}$ Sec. Cor. which is as described in original notes and from which a cross (X) cut in rock, bears N.45*W. 14 lks. dist. A fir, 8 ins. diam., bears S.75*E., 66 lks. dist., marked $\frac{1}{4}$ S B T.
79.86	Cor. to Secs. 22, 23, 26 and 27 as described in original notes. From the Cor. of Secs. 21, 22, 27, and 28, I run N.0*2'W. bet. secs. 21 and 22 tracing and remeasuring.
40.00	Found the $\frac{1}{4}$ Sec. Cor. as reported by the Examiner. I erase the markings on the N. face and mark $\frac{1}{4}$ S on W. face. The distance to the NE. bearing tree is 88 lks. dist. as reported by the examiner instead of 78 lks. as reported in original notes.
80.00	The Cor. of Secs. 15, 16, 21 and 22 as reported in original notes. From the Cor. of Secs. 15, 16, 21 and 22, I trace and remeasure and run. N.0*2'W. bet. Secs. 15 and 16 and at
40.00	Find the $\frac{1}{4}$ Sec. as reported by the Examiner. I erase the markings on the N. face and mark $\frac{1}{4}$ S on W. face.
80.00	The Cor. to Secs. 9, 10, 15 and 16, as reported in original notes on file in the U S Surveyor General's Office. From this Cor. I trace without remeasuring the surveyed lines and examine each cor. on the W and N bdrs. of the remainder of this tier of Secs. verify the witnesses thereto and where necessary correct markings thereon to correspond with notes, now on file in the U S Surveyor Generals Office.