

Corrections of Surveys in T. 26 S., R. 8 W.

CHAINS

I now return to the cor. of secs. 4, 5, 32 and 33, on the S bdy. of the Tp. which is a post marked as reported by the Examiner. I supply the omitted markings to wit: T 26 S on NE, R 8 W on SE, and T 27 S on SW faces, with 4 notches on E and 2 notches on W edges, and dug pit 18x18x12 ins. 5½ ft. dist. SW of cor. Thence N.0*3'W. bet. secs. 32 and 33 retracing with out remeasuring. ¼ sec. cor. as reported in original notes. I find the witness trees at the cor. of secs. 28, 29, 32 and 33 destroyed by fire and therefore made new ones as follows:

A fir, 12 ins. diam., bears N.50*E., 4 lks. dist., marked T 26 S R 8 W S 28 B T.

A fir, 10 ins. diam., bears S.52*E., 65 lks. dist., marked T 26 S R 8 W S 33 B T.

A fir, 14 ins. diam., bears S.57*W., 8 lks. dist., marked T 26 S R 8 W S 32 B T.

A fir, 10 ins. diam., bears N.49*W., 33 lks. dist., marked T 26 S R 8 W S 29 B T.

Thence I continue to trace without remeasuring the surveyed lines and examine each cor. on the N and W bdrs. of the fourth tier of secs. verify the witnesses thereto and where necessary correct the markings thereon to conform with the notes thereof on file in the U. S. Surveyor General's Office. Then from the cor. of secs. 5, 6, 31, and 32 on the S bdy. of the Tp. I trace without remeasuring the surveyed lines and examine each cor. on the N and W bdrs. of the fifth tier of secs. and the North bdrs. of the sixth tier W to the ¼ sec. cor. verify the witnesses thereto and where necessary correct the markings thereon to correspond to the notes thereof now on file in the U. S. Surveyor General's Office.

At the cor. of secs. 29, 30, 31 and 32, I dig new pits, 18x18x12 ins. in each sec. 5½ ft. distance