

Resurvey of the E. Bdy. of T. 26 S., R. 9 W.

CHAINS	<p>Thence I run. N.0*6'W. on a true line bet. secs. 19 and 24. Va.19*15'E.</p>	
10.00	Top of ridge and descend, bears E. and W.	
12.50	Leave old deadening; enter heavy green timber, bears E. and W.	
22.25	Spring branch, 1 lk. wide, runs W.	-100
36.50	Begin steep descent, bears E. and W..	
39.45	Brook, 5 lks. wide, runs W.	-50
40.00	<p>Set chinquapin post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{2}$ sec. cor. marked $\frac{1}{2}$ S. on W. face from which</p> <p>A fir, 48 ins. diam., bears N.45*E., 2 lks. dist., marked $\frac{1}{2}$ S B T.</p> <p>A fir, 48 ins. diam., bears N.70*W., 107 lks. dist., marked $\frac{1}{2}$ S B T.</p> <p>From this cor. the old $\frac{1}{2}$ Sec. Cor. which is a post witnessed as described by the Surveyor General, bears S. 3*W., 9.05 chs. dist. I destroy the old post and obliterate the marks on the old bearing trees.</p>	
47.00	Top of ridge, bears E. and W.	+ 70
49.90	Spring branch, 1 lk. wide, runs W.	- 50
55.00	Top of ridge, bears E. and W.	+ 20
80.00	<p>Set hemlock post. 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 13, 18, 19, and 24 marked T 26 S S 18 on NE., R 8 W S 19 on SE., S 24 on SW. and S 13 on NW. faces, with 3 notches on N. and S. edges, from which</p> <p>A hemlock, 20 ins. diam., bears N.22*30'E., 22 lks. dist., marked T 26 S R 8 W S 18 B T.</p> <p>A hemlock, 24 ins. diam., bears S.35*E., 28 lks. dist., marked T 26 S R 8 W S 19 B T.</p> <p>A hemlock, 20 ins. diam., bears S.67*15'W., 95 lks. dist., marked T 26 S R 9 W S 24 B T.</p> <p>A hemlock, 18 ins. diam., bears N.32*45'W., 52 lks. dist., marked T 26 S R 9 W S 13 B T.</p>	