

## County Surveyor's Record, Douglas County, Oregon

-1-

South Boundary of T. 26 S., R. 9 W., W.M.,  
as surveyed by John W. Meldrum, Deputy Surveyor, under contract  
No. 662, dated May 21, 1896.

CHAINS

East, on true line bet. secs. 4 and 33\*\*\*\*\*

Var. 19°15'E.

80.00

Set hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the  
ground for cor. of secs. 3, 4, 33, and 34, marked:

T. 26 S., S. 34 on N.E.,

R. 9 W., S. 34 on S.E.,

T. 27 S., S. 4 on S.W. and

S. 33 on N.W. faces, with 3 notches on E. and W.  
edges; from whichA fir, 60 ins. diam., bears N.42°E., 24 lks, dist.  
marked, T. 26 S., R. 9 W., S. 34, B.T.A fir, 56 ins. diam., bears S. 57°30'E., 52 lks. dist.  
marked, T. 27 S., R. 9 W., S. 3, B.T.A fir, 56 ins. diam., bears S.8°W., 27 lks. dist.,  
marked, T. 27 S., R. 9 W., S. 4, B.T.A fir, 60 ins. diam., bears N.70°45'W., 81 lks. dist.,  
marked, T. 26 S., R. 9 W., S. 33, B.T.This cor. is 500 ft. above the  $\frac{1}{4}$  sec. cor.

East, on true line bet. secs. 3 and 34.

Var. 19°15'E.

Ascend gentle slope from cor; through heavy timber.

17.45

Var. 19°05'E.

23.50

Top of ridge 150 ft. above sec. cor.; bears N. and S.

26.25

Ravine 30 ft. below ridge, course NW.

33.45

Top of ridge, 100 ft. above ravine; bears N and S.

38.25

Ravine 30 ft. below ridge, course SE.

40.00

Set fir post 3 ft. long, 4 ins. sq., 24 ins. in the ground

for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N face, from whichA fir, 10 ins. diam., bears N.22°45'E., 20 lks. dist.  
marked  $\frac{1}{4}$  S, B.T.A hemlock, 14 ins, diam., bears S.29°E., 15 lks.  
dist., marked  $\frac{1}{4}$  S, B.T.

42.00

Begin steep descent, bears NE &amp; SW

48.85

Descend precipice 25 ft. high; bears N &amp; S.

51.15

Descend precipice 35 ft. high; bears N &amp; S.