

County Surveyor's Record, Douglas County, Oregon

-18-

Subdivision of T. 26 S., R. 9 W.

CHAINS

dense undergrowth, 80.32 chs.

September 21, 1896.

At the cor. of secs. 26, 27, 34 and 35

Thence I run

N. 0°S'W., bet. secs. 26 and 27.

Var. 19°15'E.

Along east slope of mountain ascending gradually

19.00	Roseburgh and Coos Bay Trail, bears NE & SW.	
21.00	Top of spur, course NE.	+50
40.00	Set cedar post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N face, from which A hemlock, 30 ins. diam., bears S.74°30'W., 73 lks. dist. marked $\frac{1}{4}$ S, B.T. A fir, 60 ins. diam., bears S.5°15'E., 193 lks. dist. marked $\frac{1}{4}$ S, B.T.	-600
46.80	Brook 3 lks. wide, runs E.	-300
47.60	Brook 2 lks. wide, runs SE	+30
56.00	Spring branch 1 lk. wide, runs SE	+350
70.00	Top of steep ascent, and ascend gradually, bears NW & SE	+450
80.00	Set chincopin post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 22, 23, 26 and 27, marked T. 26 S, S 23 on NE, R. 9 W, S 26 on SE, S 27 on SW and S 22 on NW faces, with 2 notches on S & E edges, from which A fir, 32 ins. diam., bears N.39°E., 13 lks. dist. marked T. 26 S, R. 9 W, S 23, B.T. A hemlock, 13 ins. diam., bears S.9°15'E., 20 lks. dist. marked T. 26 S, R. 9 W, S 26, B.T. A hemlock, 14 ins. diam., bears S.33°W., 49 lks. dist. marked T. 26 S, R. 9 W, S 27, B.T. A hemlock, 12 ins. diam., bears N.33°W., 47 lks. dist. marked T. 26 S, R. 9 W, S 22, B.T.	+100