

Subdivisions of T. 26 S., R. 9 W.

CHAINS		
	Descend along NE slope of spur.	
7.00	Brook 3 lks. wide, runs NW.	-125
15.00	Top of spur, course W.	+100
27.75	Brook 2 lks. wide, runs NW.	-125
32.50	Top of spur, course W.	+125
36.00	Brook 2 lks. wide, runs SW.	-125
40.00	Set hemlock post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{2}$ sec. cor. marked $\frac{1}{2}$ S on W face, from which <div style="margin-left: 40px;"> A hemlock, 13 ins. diam., bears N.72*E., 34 lks. dist. marked $\frac{1}{2}$ S B T. A maple, 10 ins. diam., bears N.21*W., 29 lks. dist. marked $\frac{1}{2}$ S B T. </div>	+125
41.59	Foot of precipice 150 ft. high; offset W 3.84 chs., thence N.0*8'W. 500 chs., thence E 3.84 chs. into line; thence S.0*8'E. 3.25 chs. top of precipice in line, which gives: 41.59 chs.+5.00 chs.-3.25 chs. equals	
43.34	Top of precipice 150 ft. high, bears E and W.	+250
53.25	Spring branch 1 lk. wide, runs SW.	
59.00	Top of spur, course W.	+100
64.75	Ravine, course NW.	-250
75.30	Top of ridge, bears N and SE.	+300
80.00	Set cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for cor. of secs. 15, 16, 21 and 22, marked T 26 S S 15 on NE, R 9 W S 22 on SE, S 21 on SW, and S 16 on NW faces, with 3 notches on S and E edges, from which <div style="margin-left: 40px;"> A fir, 13 ins. diam., bears N.42*E., 84 lks. dist. marked T 26 S R 9 W S 15 B T. A fir, 14 ins. diam., bears S.77*E., 29 lks. dist. marked T 26 S R 9 W S 22 B T. An alder, 7 ins. diam., bears S.45*W., 3 lks. dist. marked T 26 S R 9 W S 21 B T. A fir, 20 ins. diam., bears N.43*30'W., 30 lks. </div>	