

County Surveyor's Record, Douglas County, Oregon

6th Stan. Par. South of T. 27 S., R. 1 W.

CHAINS

A fir, 24 ins. diam., bears N.50\*W. 194 lks. dist. marked T 27 S R 1 W S 36 B T.

A laurel, 10 ins. diam., bears S.35\*W. 25 lks. dist. marked S B T.

Land, 3rd rate--mountainous, rough and rocky.

Timber, fir, hemlock, spruce and pine.

Very thick underbrush of vine maple, cinnamon, etc.

June 26, 1883.

Resurvey of 6th Stan. Parallel South through R. 1 W. As Surveyed by Homer D. Angell, Deputy Surveyor, under contract No. 746, dated May 5, 1902

Preliminary to commencing the subdivision of this township 27 S., R. 1 W., I run

West, on a blank line on the S. bdy. of sec. 36.

At 39.25 chs. I find the 1/4 sec. cor. on line and at 78.10 chs. the cor. of secs. 35 & 36; Therefore I continue my line west and find no part of the S. bdy. correct in measurement and that many of the corners are nearly obliterated. At 5 miles 74.08 chs. intersect N. & S. line at the cor. of Tp. 27 S., Rs. 1 and 2 W. and as Tps. 27 and 28 S., R. 1 W. have not been subdivided I resurvey the 6th standard parallel between them as follows:

June 17, 1902.

At the stan. cor. of T. 27 S., Rs. 1 W. and 1 E.

Thence I run

West, on S. bdy. of sec. 36.

Descend through heavy timber, and scattering undergrowth.

5.20 Spring branch, 10 lks. wide, course NW.

Ascend.

19.85 Top of spur, bears N. & S.

Descend.

39.27 Old 1/4 cor. on line which I destroy.

Difference between measurements of 40.00 chs. by two sets of chainmen is 6 lks. position of middle point.