

County Surveyor's Record, Douglas County, Oregon

Resurvey of 6th Stan. Parallel S. through R. 1 W.

CHAINS	<p>West, on S. bdy. sec. 35.</p> <p>Ascend through heavy timber and scattering undergrowth.</p> <p>34.50 Spring branch, 4 lks. wide, course N.</p> <p>Ascend.</p> <p>37.87 Old $\frac{1}{4}$ cor. on line which I destroy.</p> <p>Difference between measurements of 40.00 chs. by two sets of chainmen is 20 lks.; position of middle point</p> <p>By 1st set, 39.90 chs.</p> <p>By 2nd set, 40.10 chs.; the mean of which is</p> <p>40.00 Set basalt stone 15x10x10 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked S C $\frac{1}{4}$ on N. face, from which</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears NE. 35 lks. dist. marked S C $\frac{1}{4}$ S 35 B T.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S.2*E. 30 lks. dist. marked S C $\frac{1}{4}$ S 2 B T.</p> <p>63.00 Top of ridge, 200 ft. above $\frac{1}{4}$ sec. cor. bears N. & S.</p> <p>77.12 Old sec. cor. on line which I destroy.</p> <p>Difference between measurements of 80.00 chs. by two sets of chainmen is 6 lks.; position of middle point</p> <p>By 1st set, 79.96 chs.</p> <p>By 2nd set, 80.04 chs.; the mean of which is</p> <p>80.00 Set a basalt stone 12x12x6 ins., 8 ins. in ground for stan. cor. of secs. 34 & 35 marked S. C. on N. and with 2 grooves on E. and 4 grooves on W. faces, from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.56*E. 47 lks. dist. marked T 27 S R 1 W S 35 B T.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.30*W. 11 lks. dist. marked T 27 S R 1 W S 34 B T.</p> <p>Land, mountainous.</p> <p>Soil, stony and 3rd rate.</p> <p>Timber, fir, pine and hemlock.</p> <p>Undergrowth, laurel, and willow.</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth. 80.00 chs.</p>
--------	--