

County Surveyor's Record, Douglas County, Oregon

Resurvey of 6th Stan. Par. S. through R. 1 W.

CHAINS	
	West, on S. bdy. sec. 34.
	Descend through heavy timber and scattering undergrowth.
2.40	Spring branch, 3 lks. wide, course NW.
	Thence along N. slope.
35.10	Spring branch, 10 lks. wide, good water, course NE.
36.12	Old $\frac{1}{4}$ cor. on line which I destroy.
	Difference between measurements of 40.00 chs. by two
	sets of chainmen is 14 lks.; position of middle point
	By 1st set, 39.93 chs.
	By 2nd set, 40.07 chs.; the mean of which is
40.00	Set a hemlock post, 3 ft. long, 3 ins. sq. 24 ins. in the
	ground for stan. $\frac{1}{4}$ sec. cor. marked S. C. $\frac{1}{4}$ S. 34 on
	N. face and 3 on S. face, from which
	A fir, 30 ins. diam., bears N.7*E. 36 lks. dist.
	marked S C $\frac{1}{4}$ S 34 B T.
	A hemlock, 12 ins. diam., bears S.8*E. 12 lks. dist.
	marked S C $\frac{1}{4}$ S 3 B T.
57.62	Spring branch, 2 lks. wide, course NE.
73.00	Foot of descent.
73.25	Spring branch, 15 lks. wide, course NE.
	Ascend steep bank.
76.12	Old sec. cor. on line which I destroy.
	Difference between measurements of 80.00 chs. by two
	sets of chainmen is 18 lks.; position of middle point
	By 1st set, 80.09 chs.
	By 2nd set, 79.90 chs., the mean of which is
80.00	Set a hemlock post, 3 ft. long and 4 ins. sq., 24 ins.
	in the ground for stan. sec. cor. of secs. 33 & 34,
	marked S C T 27 S R 1 W on N., S 34 on E. and S 33 on
	W. faces with 2 grooves on E. and 4 grooves on W. faces,
	from which
	A sugar pine, 40 ins. diam., bears N.40*E. 11 lks.
	dist., marked T 27 S R 1 W S 34 B T.
	A fir, 12 ins. diam., bears N.14 $\frac{1}{2}$ *W. 58 lks. dist.
	marked T 27 S R 1 W S 33 B T.