

County Surveyor's Record, Douglas County, Oregon

Resurvey of 6th Stan. Par. S. through R. 1 W.

CHAINS

with 4 grooves on E. and 2 grooves on W. faces, from which

A fir, 10 ins. diam., bears N.56\*E. 25 lks. dist. marked T 27 S R 1 W S 33 B T.

A fir, 18 ins. diam., bears N.42\*W. 43 lks. dist. marked T 27 S R 1 W S 32 B T.

Land, mountainous.

Soil, stony, 3rd rate.

Timber, fir, pine and hemlock.

Undergrowth, laurel & willow.

Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.

West, on S. bdy. of sec. 32.

Ascend N. slope through heavy timber and dense undergrowth.

22.50 Top of divide, 200 ft. above sec. cor., course SE, and NW.

Thence along S. slope.

35.98 Old 1/4 sec. cor. on line which I destroy.

Difference between measurement of 40.00 chs. by two sets of chainmen is 16 lks.; the position of middle point By 1st set, 40.08 chs.

By 2nd set, 39.92 chs., the mean of which is

40.00 A basalt stone 18x12x6 ins., 14 ins. in the ground for stan. 1/4 sec. cor., marked S C 1/4 on N. face, from which

A fir, 18 ins. diam., bears S.32\*W. 15 lks. dist. marked S C 1/4 S 5 B T.

A fir, 16 ins. diam., bears NW. 14 lks. dist. marked S C 1/4 S 32 B T.

76.00 Old stan. sec. cor. on line which I destroy.

Difference between measurements of 80.00 chs. by two sets of chainmen is 12 lks.; the position of middle point

By 1st set, <sup>80.</sup>40.06 chs.

By 2nd set, <sup>79</sup>39.94 chs., the mean of which is