

County Surveyor's Record, Douglas County, Oregon

Resurvey of 6th Stan. Par. S. through R. 1 W.

CHAINS

- 80.00 Set a basalt stone 12x8x6 ins., 8 ins. in the ground for stan. cor. of secs. 31 and 32, marked S C on N. with 5 grooves on E. and 1 groove on W. faces, from which
- A fir, 20 ins. diam., bears N.40*E. 32 lks. dist. marked T 27 S R 1 W S 32 B T.
- A fir, 12 ins. diam., bears N.84*W. 56 lks. dist. marked T 27 S R 1 W S 31 B T.
- Land, mountainous.
- Soil, stony, 3rd rate.
- Timber, fir, pine and cedar.
- Undergrowth, laurel.
- Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.
-
- West, on S. bdy. of sec. 31.
- Along S. slope through heavy timber and dense undergrowth.
- 4.10 Spring branch, 5 lks. wide, course S.75*E.
- 35.62 Old $\frac{1}{4}$ sec. cor. on line, which I destroy
- Difference between measurements of 40.00 chs. by two sets of chainmen is 10 lks., middle point of which is
- By 1st set, 40.05 chs.
- By 2nd set, 39.95 chs., the mean of which is
- 40.00 Set basalt stone 12x10x8 ins., 8 ins. in ground for stan. $\frac{1}{4}$ sec. cor. marked S C $\frac{1}{4}$ on N. face, from which
- A fir, 30 ins. diam., bears N.10*E. 55 lks. dist. marked S C $\frac{1}{4}$ S 31 B T.
- A fir, 20 ins. diam., bears S.15*W. 8 lks. dist. marked S C $\frac{1}{4}$ S 6 B T.
- 59.00 Top of divide, 250 ft. above sec. cor., course N. & S. Thence along S. slope over precipitous ground.
- 74.10 Intersect stan. Tp. cor. for Tps. 27 S., Rs. 1 and 2 W. which is a fir post marked and witnessed as described by the surveyor general.
- Land, mountainous.
- Soil, stony and 3rd rate.