

County Surveyor's Record, Douglas County, Oregon

Resurvey of a Portion of the W. Bdy. T. 27 S., R. 1 W.

CHAINS

of 40.00 chs. and at 409.30 chs. intersect the 6th Stan. Par. S. 3.33 chs. E. of stan. cor. of Tps. 27 S., Rs. 1 and 2 W. which is a post marked and witnessed as described by the Surveyor General.

I destroy the old stan. cor. and reestablish it at the point of intersection of the random line with the 6th Stan. Par. S. as follows:

Set a basalt stone, 15x12x10 ins., 10 ins. in the ground for stan. cor. of Tps. 27 S., Rs. 1 & 2 W., marked S C on N. and with 6 grooves on N., E. & W. faces, and raised a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Pits impracticable, from which

A fir, 16 ins. diam., bears N.71*W. 62 lks. dist.
marked T 27 S R 2 W S 36 B T.

No other trees in limits.

June 20, 1902.

At the stan. cor. of Tps. 27 S., Rs. 1 and 2 W.

Thence I run

N. on a true line bet. secs. 31 & 36.

Ascend over precipitous land, through heavy timber.

5.00 Top of divide, 100 ft. above stan. T. cor., bears E. & W.

Descend.

39.25 Spring branch, 3 lks. wide, course N.10*W.

40.00 Set basalt stone, 18x10x5 ins., 14 ins. in the ground for ¼ sec. cor. marked ¼ on W. face, from which

A fir, 14 ins. diam., bears S.49*E. 78 lks. dist.
marked ¼ S 31 B T.

A hemlock, 20 ins. diam., bears N.78*W. 104 lks. dist.
marked ¼ S 36 B T.

From this cor. the old cor. bears W. 3.00 chs. I destroy all traces of the old cor.