

County Surveyor's Record, Douglas County, Oregon

Resurvey of a Portion of W. Bdy. of T. 27 S., R. 1 W.

CHAINS	
	From this cor. the old $\frac{1}{4}$ sec. cor. bears N.87 $\frac{1}{2}$ *W., 2.20 chs. dist. I destroy the old cor.
41.00	Spring branch, 3 lks. wide, course N.75*E.
51.75	Spring branch, 5 lks. wide, course E. Ascend.
55.00	Less steep ascent.
80.00	Set basalt stone, 20x12x8 ins., 15 ins. in the ground for cor. of secs. 19, 24, 25 & 30, marked with 4 notches on the N. and 2 notches on the S. edges, from which A hemlock, 14 ins. diam., bears N.65*E. 18 lks. dist. marked T 27 S R 1 W S 19 B T. A hemlock, 8 ins. diam., bears S.40 $\frac{1}{2}$ *E. 26 lks. dist. marked T 27 S R 1 W S 30 B T. A fir, 14 ins. diam., bears S.47 $\frac{1}{2}$ *W. 55 lks. dist. marked T 27 S R 2 W S 25 B T. A dogwood, 10 ins. diam., bears N.31 $\frac{1}{2}$ *W. 20 lks. dist. marked T 27 S R 2 W S 24 B T. From this cor. the old sec. cor. bears N.83*40'W. 2.31 chs. dist. I destroy the cor. Land, mountainous. Soil, stony and 3rd rate. Timber, fir, pine, hemlock and cedar. Undergrowth, laurel. Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.
	1902.
	North, bet. secs. 19 and 24. Along E. slope through heavy timber and dense undergrowth.
29.50	Spring branch, 3 lks. wide, course E.
40.00	Set basalt stone 15x8x6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which A fir, 14 ins. diam., bears S.40*E. 37 lks. dist. marked $\frac{1}{4}$ S 19 B T. A fir, 36 ins. diam., bears N.10*W. 16 lks. dist. marked $\frac{1}{4}$ S 24 B T. From this corner the old $\frac{1}{4}$ sec. cor. bears N.44*40'W.