

County Surveyor's Record, Douglas County, Oregon

16

North Boundary of T. 27 S., R. 1 W.

CHAINS

- 40.00 Set a basalt stone 20x10x8 ins., 15 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which
- A fir, 18 ins. diam., bears S.20*W. 24 lks. dist. marked $\frac{1}{4}$ S 1 B T.
- A fir, 18 ins. diam., bears N.5*W. 25 lks. dist. marked $\frac{1}{4}$ S 36 B T.
- Ascend hillside bears SE. and NW.
- 49.50 Top of ridge, bears N. & S.
- Descend.
- 66.25 A spring branch, 3 lks. wide, course NE.
- 80.00 The cor. of Tps. 26 and 27 S., R. 1 E. and R. 1 W.
- Land, mountainous, and rolling.
- Soil, 2nd and 3rd rates.
- Timber, fir, hemlock, cedar, pine,
- Undergrowth, laurel.
- Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.

General Description

This township is rough and mountainous. The township is well watered and has an abundance of good fir and pine timber.

The north fork of the Umpqua River, or Little River, passes almost through the middle of the township from east to west into which the streams have a general trend from both north and south.

July 11. 1902.

Willamette Meridian through T. 27 S.
Same Deputy and Contract.

From the stan. cor. of Tps. 27 S., Rs. 1 E. and 1 W.

which I established June 16, 1902, I run

North, bet. secs. 31 and 36.

Along W. slope through heavy timber and scattering undergrowth.